

Silicone Lubricants – Product Characteristics

| <i>Product No.</i> | <i>Sprayon Product</i> | <i>Plastic Safe</i> | <i>NSF Rating</i> | <i>Temperature Rating</i> | <i>Paintable</i> | <i>Viscosity</i> | <i>Chlorinated Solvents</i> | <i>% Actives</i> | <i>O.D.P.</i> |
|--------------------|-----------------------------|---------------------|-------------------|---------------------------|------------------|------------------|-----------------------------|------------------|---------------|
| S01324 | Premium Silicone Lube | Yes | – | 400°F | Yes | M | No | 6.6 | None |
| S00206 | All-Purpose Silicone Lube | Yes | – | 375°F | Yes | M | No | 5 | None |
| S00210 | Food-Grade Silicone Lube | Yes | H1 | 450°F | No | L | No | 5 | None |
| S00505 | Heavy-Duty Silicone Lube | No* | – | 450°F | No | H | Yes | 5 | None |
| S00510 | Economy Silicone Lube | No* | H2 | 575°F | No | L | Yes | 3.5 | None |
| S00516 | Multi-Purpose Silicone Lube | No* | – | 450°F | No | H | Yes | 1.8 | None |

*Test on non-essential piece before using.

Viscosity Range: L = Low M = Medium H = High

O.D.P.: Ozone Depletion Potential