



S00103 RUST BREAKER® PENETRANT

Penetrant that Performs Like a Wrench!

The Ultimate Choice for
Value and Performance.

- Won't Damage Seals or Bearings
- Non-Flammable Propellant

Why Choose Sprayon®?

Why use Sprayon S00103 Rust-Breaker® instead of LPS® LST 01916?

Sprayon 103 Rust-Breaker gives you a higher flash point, higher dielectric strength, much higher water displacement, greater temperature range, and higher penetration as tested by wicking.



| Comparison tests/data | Sprayon S00103 Rust-Breaker | LPS LST 01916 |
|-------------------------------|-----------------------------|---------------|
| Flash Point | 205°F | 175°F |
| Dielectric Strength | 47,400 | 44,500 |
| Water Displacement (mm) | 129 | 29 |
| Temperature Rating (high end) | 450°F | 300°F |
| Penetrating Power (wicking) | 9 | 4 |

Why use Sprayon S00103 Rust-Breaker instead of CRC® Knock'er Loose® 03020?

Sprayon 103 Rust-Breaker gives you a higher flash point, higher dielectric strength, higher water displacement, greater temperature range, and higher penetration as tested by wicking.



| Comparison tests/data | Sprayon S00103 Rust-Breaker | CRC Knock'er Loose 03020 |
|-------------------------------|-----------------------------|--------------------------|
| Flash Point | 205°F | 145°F |
| Dielectric Strength | 47,400 | 42,000 |
| Water Displacement (mm) | 129 | 106 |
| Temperature Rating (high end) | 450°F | 300°F |
| Penetrating Power (wicking) | 9 | 2 |



Why use Sprayon S00103 Rust-Breaker instead of CRC® Screwloose® 03060?

Sprayon 103 Rust-Breaker gives you a much higher flash point, higher dielectric strength, higher water displacement, greater temperature range, and higher penetration as tested by wicking.

| Comparison tests/data | Sprayon S00103 Rust-Breaker | CRC Screwloose 03060 |
|-------------------------------|-----------------------------|----------------------|
| Flash Point | 205°F | 113°F |
| Dielectric Strength | 47,400 | 43,000 |
| Water Displacement (mm) | 129 | 93 |
| Temperature Rating (high end) | 450°F | 300°F |
| Penetrating Power (wicking) | 9 | 8 |



Why use Sprayon S00103 Rust-Breaker instead of KANO Aerokroil®?

Sprayon 103 Rust-Breaker gives you a much higher flash point, far higher dielectric strength, a non-flammable propellant, higher water displacement, much greater temperature range, and higher penetration as tested by wicking. In addition, Sprayon Rust-Breaker can be used in food processing operations.

| Comparison tests/data | Sprayon S00103 Rust-Breaker | KANO Aerokroil |
|-------------------------------|-----------------------------|----------------|
| Flash Point | 205°F | 153°F |
| Dielectric Strength | 47,400 | 22,000 |
| Non-Flammable Propellant? | Yes | No |
| Water Displacement (mm) | 129 | 90 |
| Temperature Rating (high end) | 450°F | 120°F |
| Penetrating Power (wicking) | 9 | 7 |
| NSF Rating | H2 | None |



Why Choose Sprayon®?



Why use Sprayon S00103 Rust-Breaker instead of PB™ B'laster® 16-PB?

Sprayon 103 Rust-Breaker gives you a higher flash point, higher dielectric strength, higher water displacement, a much greater temperature range, and higher penetration as tested by wicking. In addition, Sprayon Rust-Breaker can be used in food processing operations.

| Comparison tests/data | Sprayon S00103 Rust-Breaker | PB B'laster 16-PB |
|-------------------------------|-----------------------------|-------------------|
| Flash Point | 205°F | 152°F |
| Dielectric Strength | 47,400 | 36,500 |
| Water Displacement (mm) | 129 | 62 |
| Temperature Rating (high end) | 450°F | 170°F |
| Penetrating Power (wicking) | 9 | 6 |
| NSF Rating | H2 | None |

Why use Sprayon S00103 Rust-Breaker instead of Liquid Wrench® L212?

Sprayon 103 Rust-Breaker has a lower HMIS rating, a higher flash point, higher dielectric strength, much greater water displacement properties, better penetration power, and Rust-Breaker can be used in food processing operations.



| Comparison tests/data | Sprayon S00103 Rust-Breaker | Liquid Wrench L212 |
|-----------------------------|-----------------------------|--------------------|
| HMIS data | 2,1,0 | 2,2,0 |
| Flash Point | 205°F | 126°F |
| Dielectric Strength | 47,400 | 39,000 |
| Water Displacement (mm) | 129 | 28 |
| Penetrating Power (wicking) | 9 | 4 |
| NSF Rating | H2 | None |

S00103 Rust Breaker Penetrant

- NSF reg. no. 115050; H2 rated
- Quickly loosens rust while penetrating grease and dirt
- Transparent, non-staining oil
- Light film displaces moisture and acts as a corrosion preventative
- Jet stream sprays up to two feet for safe, accurate application
- Non-flammable propellant
- Flashpoint: 205°F
- Dielectric strength: 47,400 volts
- Will not harm painted surfaces

Uses: For releasing rusted or frozen lugs and bolts, lubricating tight-fitting parts, general overhaul, repair work, food plant equipment.

16-oz. cans (12-oz. net wt.)
Case Pack: 12

AVAILABLE IN BULK:
S10301 - 1-gallon container
S10305 - 5-gallon pail

Distributed By:

LPS is a registered trademark of Illinois Tool Works.
CRC, Knock'er Loose and Screwloose are registered trademarks of CRC Industries, Inc.
Aerokroil is a registered trademark of Kano Laboratories.
PB B'laster are registered trademarks of B'laster/P.C.C.I.
Liquid Wrench is a registered trademark of Radiator Speciality Company.
Sprayon and Rust Breaker are registered trademarks of The Sherwin-Williams Company.



Krylon Products Group • Cleveland, OH 44115
www.KPG-Industrial.com
©2005 Krylon Products Group SIS-6038 (Rev. 6/05)